

Incara™ Disq'In - German standard

for offices and meeting rooms



Technical characteristics p. 1104

For flush-mounting in furniture, compatible desktop thickness 15 to 40 mm
Dimensions optimised by remote terminal blocks
2 m cord with 2P+E plug
HDMI sockets: feedthrough sockets
Snap-on fixing via retractable claws

Pack	Cat.Nos	Incara Disq'In
		2P+E sockets 16 A 250 V~ equipped with safety shutters, conforming to standard IEC 60884-1 USB chargers: 110/240 V~ 50/60 Hz power supply, conforming to standard IEC 62368-1 With 2 m cord and 2P+E plug Finishing plate to be ordered separately
		2-gang Composition: - 1 x 2P+E flush socket - 1 x 15 W USB Type-A + Type-C charger
1	6 547 46	○ White wiring accessories
1	6 547 49	● Black wiring accessories
		3-gang Composition: - 2 x 2P+E flush sockets - 1 x 15 W USB Type-A + Type-C charger
1	6 547 47	○ White wiring accessories
1	6 547 50	● Black wiring accessories
		4-gang Composition: - 2 x 2P+E flush sockets - 1 x HDMI socket - 1 x 15 W USB Type-A + Type-C charger
1	6 547 48	○ White wiring accessories
1	6 547 51	● Black wiring accessories
		Incara Disq'In finishing plates
		Metal
		2-gang
1	6 547 55	● Metal
1	6 547 56	○ White
1	6 547 57	● Black
		3-gang
1	6 547 59	● Metal
1	6 547 60	○ White
1	6 547 61	● Black
		4-gang
1	6 547 63	● Metal
1	6 547 64	○ White
1	6 547 65	● Black

Incara™ Pop-up - German standard

for offices and meeting rooms



Technical characteristics p. 1105

For flush-mounting in furniture, compatible desktop thickness 15 to 40 mm
Metal. Protective film

Pack	Cat.Nos	Incara Pop-up to be equipped
		To be equipped with Mosaic functions
		4 modules
1	6 548 00	● Brushed Aluminium
1	6 548 01	○ White
1	6 548 02	● Black
1	6 548 03	● Aluminium
1	6 548 12	● Brushed Aluminium (IP 44)
		2 x 4 modules
1	6 548 04	● Brushed Aluminium
1	6 548 05	○ White
1	6 548 06	● Black
1	6 548 07	● Aluminium
		8 modules
1	6 548 08	● Brushed Aluminium
1	6 548 09	○ White
1	6 548 10	● Black
1	6 548 11	● Aluminium
		Incara Pop-up pre-equipped
		2P+E sockets 16 A 250 V~ equipped with safety shutters, conforming to standard IEC 60884-1 USB chargers: 110/240 V~ 50/60 Hz power supply, conforming to standard IEC 62368-1 With 2 m cord and 2P+E plug
		4 modules
1	6 548 28	Composition: 1 x 2P+E socket + 1 x USB Type-C 30 W Power Delivery charger ● Brushed Aluminium
1	6 548 22	Composition: 1 x 2P+E flush socket + 1 x 15 W USB Type-A + Type-C charger ● Brushed Aluminium
1	6 548 23	Composition: 1 x 2P+E flush socket + 1 x 15 W USB Type-A + Type-C charger ○ White
		2 x 4 modules
		Composition: 2 x 2P+E flush sockets + 2 x 15 W USB Type-A + Type-C chargers
1	6 548 24	● Brushed Aluminium
1	6 548 25	○ White

Other configurations, socket standards and finishes available on request or via the pCon software

Red catalogue numbers: New products